



Extract-All™
An exclusive Air Impurities
Removal Systems, Inc. brand

EXTRACT-ALL ADSORPTION MEDIA BLENDS



PA Media Blend

Description: PA is a high activity, specially impregnated activated carbon.

Applications: It is ideally suited for use in vapor-phase ammonia applications.

PHYSICAL PROPERTIES BASE MATERIAL

Activity for CCL ₄ (ASTM D-3467)	60%
Bulk Density, Typical	30 LBS/CU FT.
Ball Pan Hardness (ASTM D3082-79)	95 Minimum

FINISHED PRODUCT

Bulk Density, Typical	42 LBS/CU FT.
Ammonia (NH ₃) Removal	16%*

*Equals 30% of the weight of the base of activated carbon before treatment

This information has been gathered from standard reference materials and/or test procedures and is believed to be true and accurate. It is offered solely for your Consideration and verification. None of the information presented shall be construed as constituting a warranty or representation, expressed, written, or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes, or that its use does not conflict with existing patent rights. No license is granted to infringe on any patent rights or practice any patent invention.

Images shown above are for illustration purposes only and are not intended to represent every type of adsorption media blend.

Air Impurities Removal Systems, Inc.
166 North 121st Street, Wauwatosa, Wisconsin 53226-3802
800.236.1889 • Phone 414.257.1770 • Facsimile 414.257.3594
sales@airsystems-inc.com • www.airsystems-inc.com