



Extract-All™
An exclusive Air Impurities
Removal Systems, Inc. brand

Series 981 HEPA Grade Air Filters



Features:

- Temp (continuous): min -15° F (-26° C) max 220° F (104° C)
- Filter change out differential: 10"-15" in. H2O above initial delta P
- Less maintenance
- More durable than paper media
- Moisture resistant
- Handles hot air and oil mist from unload cycle of reciprocating/piston compressor
- Reinforced with epoxy coated steel wire on both sides of cloth
- Dust loading capacity is increased 40 % - 50% with prefilter
- Optimal sealing surface & design
- Heavy duty industrial strength glass surrounded by heavy gauge expanded metal
- Maximum oversize required to minimize pressure drop

Efficiency:

99.97% removal efficiency standard to 0.3

Typical Applications:

Healthcare, Biotech, Pharmaceutical, Food Processing, Semiconductor, Biomedical, Universities, Laboratories, Industrial Applications, Photo Processing, Mushroom Growers, Research

| MEDIA | RATED FLOW | SURFACE AREA | ID | OD | HT |
|-------|------------|--------------|------|------|------|
| HEPA | 308 | 35.50 | 6.00 | 9.75 | 9.63 |

Air Impurities Removal Systems, Inc.
166 North 121st Street, Wauwatosa, Wisconsin 53226-3802
800.236.1889 • Phone 414.257.1770 • Facsimile 414.257.3594
sales@airsystems-inc.com • www.airsystems-inc.com