



Extract-All™
An exclusive Air Impurities
Removal Systems, Inc. brand

95% Primary Rigid Cell Filters for Extract-All™ Series 984 and 987



Features:

- Designed for medium and high efficiency applications
- Superior service life
- Total Rigid construction makes it ideal for variable air volume systems where changes in airflow can have an adverse affect on non-rigid type filters
- Synthetic Media
- Ideal for High Humidity Applications
- Injection Molded Pleat Separators
- Galvanized Steel Frame
- Box Style
- High Dust Holding Capacity
- Rated to withstand temperatures up to 180 degrees Fahrenheit
- Classified under U.L. std. 900

Efficiency:

90 – 95% efficiency – MERV 14

Typical Applications:

Brazing, Light Welding, Plastic Heat Bending, Polishing Applications, Powder Weighing, Robotic Welding, Sanding Operations, Small Grinding Operations, Soldering, Toxic Particulate, Toxic Powders, Wire Stripping

FILTER DEPTH	RATED VELOCITY FPM	INITIAL RESIST. IN. W.G.	FINAL RESIST. IN. WG	MEDIA SQUARE FEET
6”	250	.29	1.50	13.20 – 26.39
12”	500	.55	1.50	29.17 – 58.33

Air Impurities Removal Systems, Inc.
166 North 121st Street, Wauwatosa, Wisconsin 53226-3802
800.236.1889 • Phone 414.257.1770 • Facsimile 414.257.3594
sales@airsystems-inc.com • www.airsystems-inc.com