



Extract-All™

An exclusive Air Impurities
Removal Systems, Inc. brand

Extract-All™ Accessories

Rigid Flex Hose

RIGID INTERLOCKED DUCT HOSE WITH CHANGEABLE ID

TEMPERATURE RANGES: -30°F to 180°F

APPLICATIONS: Rigid duct hose with interlock construction which allows inside diameter to be changed by twisting hose. Used in applications such as spot coolers, clean room venting, fume and dust removal, and elbows for rigid pipe. Extract-All™ Rigid Flex can be bent into a fixed position to direct blowing or suction of air, gasses, vapors, fumes, or mists.

CONSTRUCTION: Interlocked polypropylene

COLOR CHOICE: Black or White



Specifications

I.D., Inches	2.5	3	4	5	6	8	10	12
O.D., Inches	2.80	3.23	4.20	5.20	6.16	8.06	10.21	12.07
PITCH, Inches								
MINIMUM BENDING RADIUS								
72 degrees F, Inches	6.0	7.0	11.0	14.0	15.0	20.0	27.0	32.0
WORKING PRESSURE 72								
degrees F, P.S.I.								
VACUUM RATING 72								
degrees F, In. Hg								
WEIGHT, Lbs./Ft.	0.35	0.36	0.52	0.76	0.79	1.07	1.52	1.68
STANDARD LENGTH, Ft.	20	20	20	20	20	20	10	10

AIR IMPURITIES REMOVAL SYSTEMS, INC.
166 N. 121st Street • Wauwatosa, Wisconsin 53226
Toll Free: (800) 236.1889
Phone: (414) 257.1770 • Fax: (414) 257.3594
info@airsystems-inc.com • www.airsystems-inc.com



Extract-All™
An exclusive Air Impurities
Removal Systems, Inc. brand